

Transactions

Introduction

Bank

1. getConnection/setConnection

```
package transactions_1;
import java.sql.*;
public class Bank {

    public Connection getConnection(String jdbcDriverName,
                                   String jdbcURL) {
        try {
            Class.forName(jdbcDriverName);
            return DriverManager.getConnection(jdbcURL);
        } catch (ClassNotFoundException ex) { ex.printStackTrace(); }
        } catch (SQLException ex) { ex.printStackTrace(); }
        return null;
    }

    public void releaseConnection(Connection conn) {
        if (conn!=null)
            try {
                conn.close();
            } catch (SQLException ex) { ex.printStackTrace(); }
    }
}
```

Bank

2. deposit/withdraw

```
public void deposit(int account, double amount, Connection conn)
    throws SQLException{
    String sql="UPDATE Account SET Balance = Balance + "+ amount+
        "WHERE AccountId = "+account;
    Statement stmt=conn.createStatement();
    stmt.executeQuery(sql);
    System.out.println("Deposited "+amount+" to account "+account);
}

public void withdraw(int account, double amount, Connection conn)
    throws SQLException{
    String sql="UPDATE Account SET Balance = Balance - "+ amount+
        "WHERE AccountId = "+account;
    Statement stmt=conn.createStatement();
    stmt.executeQuery(sql);
    System.out.println("Withdrew "+amount+" from account "+
        account);
}
```

Bank

3. printBalance

```
public void printBalance(Connection conn) {
    ResultSet rs=null;
    Statement stmt=null;
    try {
        stmt=conn.createStatement();
        rs=stmt.executeQuery("SELECT * FROM Account");
        while (rs.next())
            System.out.println("Account "+rs.getInt(1)+
                " has a balnce of "+rs.getDouble(2));
    } catch (SQLException ex) { ex.printStackTrace(); }
    finally {
        try {
            if (rs!=null)
                rs.close();
            if (stmt!=null)
                stmt.close();
        } catch (SQLException ex) { ex.printStackTrace(); }
    }
}
```

```
public void transferFunds(int fromAccount, int toAccount,
                          double amount, Connection conn){
    Statement stmt=null;
    try {
        withdraw(fromAccount, amount, conn);
        deposit(toAccount,amount,conn);
    }
    catch (SQLException ex) {
        System.out.println("An error occured!");
        ex.printStackTrace();
    }
}
```

```
public static void main(String[] args) {
    if (args.length <3) {
        System.exit(1);
    }
    Connection conn=null;
    Bank bank = new Bank();
    try {
        conn=bank.getConnection(args[0],args[1]);
        bank.transferFunds(1,2,Double.parseDouble(args[2]),conn);
        bank.printBalance(conn);
    } catch (NumberFormatException ex) { ex.printStackTrace();
    } finally {bank.releaseConnection(conn);}
}
```

Bank

transferFunds – fixed version!


```
public void transferFunds(int fromAccount, int toAccount,
                          double amount, Connection conn){
    Statement stmt=null;
    try {
        conn.setAutoCommit(false);
        withdraw(fromAccount, amount, conn);
        deposit(toAccount, amount, conn);
        conn.commit();
    }
    catch (SQLException ex) {
        System.out.println("An error occurred!");
        ex.printStackTrace();
        try {
            conn.rollback();
        } catch (SQLException e) { e.printStackTrace(); }
    }
}
```

TRANSACTION

Actors

A **transactional object** (or **transactional component**) is an application component that is involved in a transaction. A **transaction manager** is responsible for managing the transactional operations of the transactional components. A **resource** is a persistent storage from which you read or write. A **resource manager** manages a resource. Resource managers are responsible for managing all state that is permanent. The most popular interface for resource managers is the **X/Open XA** resource manager interface (a de facto standard): a deployment with heterogeneous resource managers from different vendors can interoperate.

Distributed Systems



Who begins a transaction?

Who begins a transaction? Who issues either a commit or abort?
This is called **demarcating transactional boundaries**.

There are three ways to demarcate transactions:

- programmatically:**

you are responsible for issuing a *begin* statement and either a *commit* or an *abort* statement.

- declaratively,**

the EJB container *intercepts* the request and starts up a transaction automatically on behalf of your bean.

- client-initiated.**

write code to start and end the transaction from the client code outside of your bean.

Programmatic vs. declarative

programmatic transactions:

your bean has full control over transactional boundaries. For instance, you can use programmatic transactions to run a series of minitransactions within a bean method.

When using programmatic transactions, always try to complete your transactions in the same method that you began them. Doing otherwise results in spaghetti code where it is difficult to track the transactions; the performance decreases because the transaction is held open longer.

declarative transactions:

your entire bean method must either run under a transaction or not run under a transaction.

Transactions are simpler! (just declare them in the descriptor)

Client-initiated

Client initiated transactions:

A nontransactional remote client calls an enterprise bean that performs its own transactions. The bean succeeds in the transaction, but the network or application server crashes before the result is returned to a remote client. The remote client would receive a Java RMI RemoteException indicating a network error, but would not know whether the transaction that took place in the enterprise bean was a success or a failure.

With client-controlled transactions, if anything goes wrong, the client will know about it.

The downside to client-controlled transactions is that if the client is located far from the server, **transactions are likely to take a longer time and the efficiency will suffer.**

Transactions

ACID

The ACID Properties


Atomicity guarantees that many operations are bundled together and appear as one contiguous unit of work .

Consistency guarantees that a transaction leaves the system 's state to be consistent after a transaction completes.


Isolation protects concurrently executing transactions from seeing eachother 's incomplete results.

Durability guarantees that updates to managed resources, such as database records, survive failures. (Recoverable resources keep a transactional log for exactly this purpose. If the resource crashes, the permanent data can be reconstructed by reapplying the steps in the log.)


Lost Update




Dirty Read



Unrepeatable Read



Phantom Read (ghost update)



Isolation levels

ISOLATION LEVEL	Dirty Read	Unrepeatable Read	Phantom Read
READ UNCOMMITTED	SI	SI	SI
READ COMMITTED	NO	SI	SI
REPEATABLE READ	NO	NO	SI
SERIALIZABLE	NO	NO	NO

Default level for many DBMS

Isolation levels

BMT:

you specify isolation levels with your resource manager API (such as JDBC).

For example, you could call `java.sql.Connection.SetTransactionIsolation(...)`.

CMT:

there is no way to specify isolation levels in the deployment descriptor.

You need to either use resource manager APIs (such as JDBC), or rely on your container's tools or database's tools to specify isolation.

Isolation portability problems

Unfortunately, there is no way to specify isolation for container-managed transactional beans in a portable way—you are reliant on container and database tools.

This means if you have written an application, you cannot ship that application with built-in isolation. The deployer now needs to know about transaction isolation when he uses the container's tools, and the deployer might not know a whole lot about your application's transactional behavior.

Pessimistic and Optimistic Concurrency Control Strategies

TIPO	Dimension	Concurrency	Problems
Pessimistic —Your EJB locks the source data for the entire time it needs data, not allowing anything else to potentially update the data until it completes its transaction.	Small Systems	Low	Does not scale well
Optimistic - Your EJB implements a strategy to detect whether a change has occurred to the source data between the time it was read and the time it now needs to be updated. Locks are placed on the data only for the small periods of time the EJB interacts with the database.	Large Systems	High	Complexity of the collision detection code

Transactions

Transactions e EJB

Transactional Models

A **flat transaction** is the simplest transactional model to understand. A flat transaction is a series of operations that are performed atomically as a single *unit of work*.

A **nested transaction** allows you to embed atomic units of work within other units of work. The unit of work that is nested within another unit of work can roll back without forcing the entire transaction to roll back.
(*subtransactions can independently roll back without affecting higher transactions in the tree*)

(Not currently mandated by the EJB specification)

Other models: **chained transactions** and **sagas**.
(Not supported by the EJB specification)

EJB Transaction Attribute Values

Required

You want your method to always run in a transaction.

If a transaction is already running, your bean joins in on that transaction. If no transaction is running, the EJB container starts one for you.

Never

Your bean cannot be involved in a transaction.

If the client calls your bean in a transaction, the container throws an exception back to the client (java.rmi.RemoteException if remote, javax.ejb.EJBException if local).

EJB Transaction Attribute Values

Supports

The method runs only in a transaction if the client had one running already —it joins that transaction.

If the client does not have a transaction, the bean runs with no transaction at all.

Mandatory

a transaction must be already running when your bean method is called. If a transaction isn't running,

javax.ejb.TransactionRequiredException is thrown back to the caller (or javax.ejb.TransactionRequiredLocalException if the client is local).

EJB Transaction Attribute Values

NotSupported

your bean cannot be involved in a transaction at all.

For example, assume we have two enterprise beans, A and B. Let's assume bean A begins a transaction and then calls bean B. If bean B is using the NotSupported attribute, the transaction that A started is suspended. None of B's operations are transactional, such as reads/writes to databases. When B completes, A's transaction is resumed.

EJB Transaction Attribute Values

RequiresNew

*You should use the RequiresNew attribute if you **always want a new transaction to begin** when your bean is called. If a transaction is already underway when your bean is called, that transaction is suspended during the bean invocation.*

The container then launches a new transaction and delegates the call to the bean. The bean performs its operations and eventually completes. The container then commits or aborts the transaction and finally resumes the old transaction. If no transaction is running when your bean is called, there is nothing to suspend or resume.

EJB Transaction Attribute Values

TIPO	PRECONDIZIONE	POSTCONDIZIONE
Required	Nessuna transazione	NUOVA
	PRE-ESISTENTE	PRE-ESISTENTE
RequiresNew	Nessuna transazione	NUOVA
	PRE-ESISTENTE	NUOVA
Supports	Nessuna transazione	Nessuna transazione
	PRE-ESISTENTE	PRE-ESISTENTE
Mandatory	Nessuna transazione	error
	PRE-ESISTENTE	PRE-ESISTENTE
NotSupported	Nessuna transazione	Nessuna transazione
	PRE-ESISTENTE	Nessuna transazione
Never	Nessuna transazione	Nessuna transazione
	PRE-ESISTENTE	error

EJB Transactions - annotation

Class annotation:

```
@TransactionManagement(  
    javax.ejb.TransactionManagementType.CONTAINER)
```

Method annotation:

```
@TransactionAttribute(  
    javax.ejb.TransactionAttributeType.REQUIRED)
```

EJB Transaction Attribute Values

```
<assembly-descriptor>
  <container-transaction>
    <method>
      <ejb-name>Employee</ejb-name>
      <method-name>*</method-name>
    </method>
    <trans-attribute>Mandatory</trans-attribute>
  </container-transaction>
  <container-transaction>
    <method>
      <ejb-name>Employee</ejb-name>
      <method-name>setName</method-name>
      <method-param>String</method-param>
    </method>
    <trans-attribute>Required</trans-attribute>
  </container-transaction>
</assembly-descriptor>
```

Transactions and Session Beans

stateful session beans:

it is possible that the business method that started a transaction completes without committing or rolling back the transaction. In such a case, the Container must retain the association between the transaction and the instance across multiple client calls until the instance commits or rolls back the transaction. When the client invokes the next business method, the Container must invoke the business method in this transaction context.

If a *stateless* session bean instance starts a transaction in a business method, it **must commit** the transaction **before the business method returns**.