



Animation in JavaFX

Horse in Motion



HorseInMotion

Horse in Motion



Copyright, 1878, by MUYBRIDGE.

MORSE'S Gallery, 417 Montgomery St., San Francisco.

THE HORSE IN MOTION.

Illustrated by
MUYBRIDGE.


AUTOMATIC ELECTRO-PHOTOGRAPHY

"SALLIE GARDNER," owned by LELAND STANFORD; running at a 1.40 gait over the Palo Alto track, 19th June, 1878.

The negatives of these photographs were made at intervals of twenty-seven inches of distance, and about the twenty-fifth part of a second of time; they illustrate consecutive positions assumed in each twenty-seven inches of progress during a single stride of the mare. The vertical lines were twenty-seven inches apart; the horizontal lines represent elevations of four inches each. The exposure of each negative was less than the two-thousandth part of a second.

Esempio di Animation

```
public void start(Stage primaryStage) {  
    final String content = "Animazioni Java FX";  
    final Text text = new Text(10, 20, "");  
    final Animation animation = new Transition() {  
        { setCycleDuration(Duration.millis(2000)); } //constructor  
        protected void interpolate(double frac) {  
            final int length = content.length();  
            final int n = Math.round(length * (float) frac);  
            text.setText(content.substring(0, n));  
        }  
    };  
    StackPane root = new StackPane();  
    root.getChildren().add(text);  
    Scene scene = new Scene(root, 300, 250);  
    primaryStage.setScene(scene);  
    primaryStage.show();  
    animation.play();  
}
```



SimpleTransitionDemo

Animation

- provides the core functionality of all animations used in the JavaFX runtime.
- Methods:
 - `play()`
 - `playFromStart()`
 - `pause()` (keeps the play head to the current position)
 - `stop()` (reset its play head to the initial position)
- The Animation progresses in the direction and speed specified by `rate`
- An animation can run in a loop by setting `cycleCount`.
- An animation with indefinite duration (a `cycleCount` of `INDEFINITE`) runs repeatedly
- If the `autoReverse` –flag is set, the animation run back and forth while looping

subclasses: **Transition** and **Timeline**

Transition

Offers a simple framework to define animation, and provides all the basic functionality defined in Animation.

- Transition requires:
 - the implementation of a method `interpolate(double)` which is called in each frame, while the Transition is running.
 - to set the `duration` of a single cycle with `Animation.setCycleDuration(javafx.util.Duration)`.

Esempio di Transition

```
public void start(Stage primaryStage) {  
    final String content = "Lorem ipsum";  
    final Text text = new Text(10, 20, "");  
    final Animation animation = new Transition() {  
        { setCycleDuration(Duration.millis(2000)); }  
        protected void interpolate(double frac) {  
            final int length = content.length();  
            final int n = Math.round(length * (float) frac);  
            text.setText(content.substring(0, n));  
        }  
    };  
    StackPane root = new StackPane();  
    root.getChildren().add(text);  
    Scene scene = new Scene(root, 300, 250);  
    primaryStage.setScene(scene);  
    primaryStage.show();  
    animation.play();  
}
```

Come cambiare le coordinate di un oggetto posizionato da un Pane?

public final double **getTranslateX()**

Gets the value of the property `translateX`.

Property description:

Defines the x coordinate of the translation that is added to this Node's transform.

The node's final translation will be computed as `layoutX + translateX`, where **layoutX** establishes the node's stable position and `translateX` optionally makes dynamic adjustments to that position.

Layout e Translate properties

- `getLayoutX`
- `setTranslateX`
- `getTraslateX`
- stesso per Y

Timeline

- A Timeline can be used to define a free from animation of any WritableValue, e.g. all JavaFX Properties.
- A Timeline, defined by one or more KeyFrames, processes individual KeyFrame sequentially, in the order specified by KeyFrame.time. The animated properties, defined as key values in KeyFrame.values, are interpolated to/from the targeted key values at the specified time of the KeyFrame to Timeline's initial position, depends on Timeline's direction.
- Timeline processes individual KeyFrame at or after specified time interval elapsed, it does not guarantee the timing when KeyFrame is processed.
- If a KeyFrame is not provided for the time==0s instant, one will be synthesized using the target values that are current at the time Animation.play() or Animation.playFromStart() is called.

KeyFrame

Defines target values at a specified point in time for a set of variables that are interpolated along a Timeline.

The developer controls the interpolation of a set of variables for the interval between successive key frames by providing a **target value** and an **Interpolator** associated with each variable. The variables are interpolated such that they will reach their target value at the specified time.

An **onFinished** function is invoked on each KeyFrame if one is provided.

Esempio di animazione 1.1

```
public class BallAnimation1 extends Application {  
    int dx = 1;  
    int dy = 1;  
    double frameDuration=0.05;  
    @Override  
    public void start(final Stage primaryStage) {  
        primaryStage.setTitle("Animation");  
        Group root = new Group();  
        Scene scene = new Scene(root, 400, 300, Color.WHITE);  
        primaryStage.setScene(scene);  
        addBall(scene);  
        primaryStage.show();  
    }  
    private void addBall(final Scene scene) { ... }  
}
```

```
public static void main(String[] args) {  
    Application.launch(args);  
}
```

Esempio di animazione 1.2 v-1

```
private void addBall(final Scene scene) {
    final Circle ball = new Circle(50, 50, 20);
    final Group root = (Group) scene.getRoot();
    root.getChildren().add(ball);
    Timeline tl = new Timeline();
    tl.setCycleCount(100); //Animation.INDEFINITE);
    KeyFrame moveBall = new KeyFrame(Duration.seconds(frameDuration),
        new EventHandler<ActionEvent>() {
            public void handle(ActionEvent event) {
                ball.setTranslateX(ball.getTranslateX() + 2*dx);
                ball.setTranslateY(ball.getTranslateY() + 0*dy);
            }
        });
    tl.getKeyFrames().add(moveBall);
    tl.play();
}
```

Esempio di animazione 1.2 v-2

```
private void addBall(final Scene scene) {
    final Circle ball = new Circle(50, 50, 20);
    final Group root = (Group) scene.getRoot();
    root.getChildren().add(ball)
    Timeline tl = new Timeline();
    tl.getKeyFrames().addAll(
        new KeyFrame(Duration.ZERO, // set start position
            new KeyValue(ball.translateXProperty(), 0),
            new KeyValue(ball.translateYProperty(), 0)),
        new KeyFrame(new Duration(2000), // set end position at 4s
            new KeyValue(ball.translateXProperty(), 200),
            new KeyValue(ball.translateYProperty(), 100)),
        new KeyFrame(new Duration(4000), // set end position at 4s
            new KeyValue(ball.translateXProperty(), 200),
            new KeyValue(ball.translateYProperty(), 0))
    );
    tl.play();
}
```

Esempio di animazione – v-3

```
public void handle(ActionEvent event) {  
    double scale=ball.getScaleX();  
    if (scale>1.5) {  
        ball.setFill(Color.RED);  
        ball.setOpacity(ball.getOpacity()-0.005);  
    }  
    if (scale>2) ball.setVisible(!ball.isVisible());  
    if (scale>2.5) {  
        ball.setVisible(false);  
        tl.stop();  
    }  
    ball.setScaleX(scale+0.01);  
    //ball.setCenterX(ball.getCenterX() + 2*dx);  
    //ball.setLayoutX(ball.getLayoutX() + 2*dx);  
    ball.setTranslateX(ball.getTranslateX() + 2*dx);  
    ball.setTranslateY(ball.getTranslateY() + 1*dy);  
}
```

espansione del solo metodo
handle delle slides precedenti!

- The node's final translation will be computed as $\text{layoutX} + \text{translateX}$, where layoutX establishes the node's stable position and translateX optionally makes dynamic adjustments to that position.
- If the node is managed and has a [Region](#) as its parent, then the layout region will set layoutX according to its own layout policy. If the node is unmanaged or parented by a [Group](#), then the application may set layoutX directly to position it.

Fade Transition 1.1

```
public class FadeTransitionDemo extends Application {  
    @Override  
    public void start(final Stage primaryStage) {  
        primaryStage.setTitle("Animation");  
        Group root = new Group();  
        Scene scene = new Scene(root, 400, 300, Color.WHITE);  
        primaryStage.setScene(scene);  
        addFadingRect(scene);  
        primaryStage.show();  
    }  
    private void addFadingRect (final Scene scene) { ... }  
}
```

```
public static void main(String[] args) {  
    Application.launch(args);  
}
```

Fade Transition 1.2

```
private void addFadingRect(final Scene scene) {
    final Rectangle rect1 = new Rectangle(10, 10, 100, 100);
    rect1.setArcHeight(20);
    rect1.setArcWidth(20);
    rect1.setFill(Color.RED);
    final Group root = (Group) scene.getRoot();
    root.getChildren().add(rect1);
    FadeTransition ft = new FadeTransition(Duration.millis(1000),
        rect1);
    ft.setFromValue(1.0);
    ft.setToValue(0.0);
    ft.setCycleCount(Timeline.INDEFINITE);
    ft.setAutoReverse(true);
    ft.play();
}
```


PathTransition 1.1

```
public class PathExample extends Application {
    @Override
    public void start(Stage primaryStage) {
        Path path = drawPath();
        final Rectangle rectPath = new Rectangle(0, 0, 40, 40);
        rectPath.setArcHeight(10);
        rectPath.setArcWidth(10);
        rectPath.setFill(Color.ORANGE);
        Group root = new Group();
        root.getChildren().addAll(path, rectPath);
        Scene scene = new Scene(root, 400, 400);
        moveObjectOnPath(path, rectPath);
        primaryStage.setScene(scene);
        primaryStage.show();
    }
    drawPath() {...}
    moveObjectOnPath (...) {...}
}

public static void main(String[] args) {
    Application.launch(args);
}
```

PathTransition 1.2

```
public Path drawPath() {
    Path path = new Path();
    MoveTo moveTo = new MoveTo(); moveTo.setX(0.0f); moveTo.setY(50.0f);
    HLineTo hLineTo = new HLineTo(); hLineTo.setX(70.0f);
    QuadCurveTo quadCurveTo = new QuadCurveTo();
    quadCurveTo.setX(120.0f); quadCurveTo.setY(110.0f);
    quadCurveTo.setControlX(100.0f); quadCurveTo.setControlY(50.0f);
    LineTo lineTo = new LineTo();
    lineTo.setX(175.0f); lineTo.setY(105.0f);
    ArcTo arcTo = new ArcTo(); arcTo.setX(50.0f); arcTo.setY(50.0f);
    arcTo.setRadiusX(50.0f); arcTo.setRadiusY(50.0f);
    path.getElements().add(moveTo); path.getElements().add(hLineTo);
    path.getElements().add(quadCurveTo); path.getElements().add(lineTo);
    path.getElements().add(arcTo);
    path.getElements().add(new MoveTo(20, 120));
    path.getElements().add(new CubicCurveTo(380, 0, 380, 120, 200, 120));
    path.getElements().add(new CubicCurveTo(0, 120, 0, 240, 380, 240));
    return path;
}
```





PathTransition 1.3

```
void moveObjectOnPath(Path path, Node node) {  
    PathTransition pathTransition = new PathTransition();  
    pathTransition.setDuration(Duration.millis(4000));  
    pathTransition.setPath(path);  
    pathTransition.setNode(node);  
    pathTransition.setOrientation(  
        PathTransition.OrientationType.ORTHOGONAL_TO_TANGENT);  
    pathTransition.setCycleCount(Timeline.INDEFINITE);  
    pathTransition.setAutoReverse(true);  
    pathTransition.play();  
}
```

QuadCurveTo

```
MoveTo moveTo = new MoveTo();  
moveTo.setX(0.0f);  
moveTo.setY(0.0f);
```

```
QuadCurveTo quadTo = new QuadCurveTo();  
quadTo.setControlX(0.0f);  
quadTo.setControlY(0.0f);  
quadTo.setX(100.0f);  
quadTo.setY(50.0f);
```



Curve di Bezier Quadratiche


$$B(t) = (1 - t)^2 P_0 + 2t(1 - t)P_1 + t^2 P_2, t \in [0, 1].$$

CubicCurveTo

```
MoveTo moveTo = new MoveTo();  
moveTo.setX(0.0f);  
moveTo.setY(0.0f);
```

```
CubicCurveTo cubicTo = new CubicCurveTo();  
cubicTo.setControlX1(0.0f);  
cubicTo.setControlY1(0.0f);  
cubicTo.setControlX2(100.0f);  
cubicTo.setControlY2(100.0f);  
cubicTo.setX(100.0f);  
cubicTo.setY(50.0f);
```

Curve di Bezier Cubiche



$$B(t) = (1 - t)^3 P_0 + 3(1 - t)^2 t P_1 + 3(1 - t) t^2 P_2 + t^3 P_3, \quad t \in [0, 1].$$

Altre Transition

- FadeTransition
- FillTransition
- PathTransition
- PauseTransition
- RotateTransition
- ScaleTransition
- StrokeTransition
- TranslateTransition

Transition composition

```
SequentialTransition sq= new SequentialTransition();  
sq().addAll(fadeTransition, translateTransition, ...);
```

```
ParallelTransition pt= new ParallelTransition ();  
pt().addAll(fadeTransition, translateTransition, ...);
```

Altri esempi

- BouncingBallAnimation
- Animation
- Tree