


Q


How can you develop and deploy a servlet using Netbeans ?

Apache Tomcat in Netbeans 8.2



<https://www.oracle.com/technetwork/pt/java/javase/downloads/jdk-netbeans-jsp-3413153-ptb.html>

Create new web project



New Web Application

Steps

1. Choose Project
2. **Name and Location**
3. Server and Settings
4. Frameworks

Name and Location

Project Name:

Project Location:

Project Folder:

☐ Use Dedicated Folder for Storing Libraries

Libraries Folder:

Different users and projects can share the same compilation libraries (see Help for details).



New Web Application

Steps

1. Choose Project
2. Name and Location
3. **Server and Settings**
4. Frameworks

Server and Settings

Add to Enterprise Application:

Server:

Java EE Version:

Context Path:



New Web Application


Steps


1. Choose Project
2. Name and Location
3. Server and Settings
4. **Frameworks**

Frameworks

Select the frameworks you want to use in your web application.

- ☐ Spring Web MVC
- ☐ JavaServer Faces
- ☐ Struts 1.3.10
- ☐ Hibernate 4.3.1





New Servlet

Steps

1. Choose File Type
2. **Name and Location**
3. Configure Servlet Deployment

Name and Location

Class Name: ReadPost

Project: WebApplication01

Location: Source Packages

Package: it.unitn.disi.ronchet.myservlets

Created File: /src/java/it/unitn/disi/ronchet/myservlets/ReadPost.java

Help

New Servlet

Steps

1. Choose File Type
2. Name and Location
3. **Configure Servlet Deployment**

Configure Servlet Deployment

Register the Servlet with the application by giving the Servlet an internal name (Servlet Name). Then specify patterns that identify the URLs that invoke the Servlet. Separate multiple patterns with commas.

☐ Add information to deployment descriptor (web.xml)

Class Name: it.unitn.disi.ronchet.myservlets.ReadPost

Servlet Name: ReadPost

URL Pattern(s): /ReadPost




Initialization Parameters:

Name	Value
------	-------

New Edit... Delete

Help < Back Next > Finish Cancel

Netbeans Services



Starting and stopping Tomcat
Undeploying WebApps

@Override

```
protected void doGet(HttpServletRequest request, HttpServletResponse  
response) throws ServletException, IOException {  
    response.setContentType("text/html;charset=UTF-8");  
}
```


@Override

```
public void destroy() {  
    log("destroy executed");  
}
```

@Override

```
public void init() {  
    log("init executed");  
}
```

Logging



The screenshot shows an IDE interface with several tabs: 'Search Results', 'Usages', 'Output', 'HTTP Server Monitor', 'WebApplication01 (run)', 'Apache Tomcat 8.0.27.0 Log', and 'Apache Tomcat 8.0.27.0'. The 'Output' tab is active, displaying a series of log messages from the Apache Tomcat application context. The logs show the execution of the 'doGet' method and the 'init' method, with timestamps and thread IDs.

```
INFO [http-nio-8084-exec-146] org.apache.catalina.core.ApplicationContext.log Demo1: ==>/Applic  
INFO [http-nio-8084-exec-147] org.apache.catalina.core.ApplicationContext.log Demo1: init execut  
INFO [http-nio-8084-exec-147] org.apache.catalina.core.ApplicationContext.log Demo1: /Users/ronc  
INFO [http-nio-8084-exec-147] org.apache.catalina.core.ApplicationContext.log Demo1: doGet execu  
INFO [http-nio-8084-exec-148] org.apache.catalina.core.ApplicationContext.log Demo1: doGet execu
```



Q

What is the HTTP state problem?


HTTP is stateless

How can we keep track of who is who, and which state of the process s/he is at?


There is no way of doing it server-side...




The state problem: part 1




The state problem: part 2



The state problem: part 2 - example



The state problem: part 2 - example




Q


What are cookies ?

How do they solve the state problem?

The state problem: solution 1




The state problem: solution 2



Keeping the state by using cookies

The idea:



MEMORY

Cookies:

A Cookie is a small amount of information sent by a servlet to a Web browser, saved by the browser, and later sent back to the server.

A cookie's value can uniquely identify a client, so cookies are commonly used for session management.

A cookie has a name, a single value, and optional attributes such as a comment, path and domain qualifiers, a maximum age, and a version number.



Cookies

- The servlet sends cookies to the browser by using the `HttpServletResponse.addCookie(javax.servlet.http.Cookie)` method, which adds fields to **HTTP response headers** to send cookies to the browser, one at a time. The browser is expected to support 20 cookies for each Web server, 300 cookies total, and may limit cookie size to 4 KB each.
- The browser returns cookies to the servlet by adding fields to **HTTP request headers**. Cookies can be retrieved from a request by using the `HttpServletRequest.getCookies()` method.



Q

**Which operations can we perform
on cookies ?**

main operations on cookies

String getName() / void setName(String s)

String getValue() / void setValue(String s)

boolean getSecure / setSecure(boolean b) (encrypt the cookie)

int getMaxAge() / void setMaxAge(int i) (Positive: seconds to live. Zero: delete cookie. Negative: only as long as browser quits.)

Control cookie scope: Normally, cookies are returned only to the exact hostname that sent them.

- **String getDomain() / setDomain(String s):**
 - instruct the browser to return them to other hosts within the same domain.
- **String getPath() / void setPath(String s)**
 - restrict the path of URL which can obtain the cookie



Placing Cookies in the Response Headers

The cookie is added to the Set-Cookie response header by means of the addCookie method of HttpServletResponse. Here's an example:

```
Cookie userCookie = new Cookie("user",  
"uid1234");  
response.addCookie(userCookie);  
// before opening the body of response!  
// i.e. before any out.print
```



Reading Cookies from the Client

- To read the cookies that come back from the client, you call `getCookies` on the `HttpServletRequest`. This returns an array of `Cookie` objects corresponding to the values that came in on the `Cookie` HTTP request header.
- Once you have this array, you typically loop down it, calling `getName` on each `Cookie` until you find one matching the name you have in mind. You then call `getValue` on the matching `Cookie`, doing some processing specific to the resultant value.









Cookies

Demo: Cookies in action

Output

Chrome


Safari



All cookies have been deleted
Go to the [initial page](#).

Sorry, we do not know each other...
Please introduce yourself.
What is your name?

Cookies in action - outline



Cookies in action - 1

```
... Page index.html Welcome.java WhatsYourNameFragment.html DeleteCookiesFragment.html DeleteCookies.java...
1 <!DOCTYPE html>
2 <html>
3   <head>
4     <title>Let's meet...</title>
5     <meta charset="UTF-8">
6     <meta name="viewport" content="width=device-width, initial-scale=1.0">
7   </head>
8   <body>
9     <form method="GET" action="welcome">
10       <label for="name">Hi! What is your name?</label>
11       <input type="text" name="name">
12       <input type="submit" >
13     </form>
14   </body>
15 </html>
```

```
... Page index.html Welcome.java WhatsYourNameFragment.html DeleteCookiesFragment.html
3 <form method="GET" action="welcome">
4   <label for="name">What is your name?</label>
5   <input type="text" name="name" value="">
6   <input type="submit" >
7 </form>
```

Cookies in action - 2

```
... Page | index.html | Welcome.java | WhatsYourNameFragment.html | DeleteCookiesFragment.html | DeleteCookies.java...  
1 <form method="GET" action="deleteCookies">  
2     Delete Cookies?  
3     <input type="submit" value="Yes, Delete">  
4     <input type="submit" value="No, Do not" formaction="welcome" >  
5 </form>
```

```
Files | Servi... | ...java | WhatsYourNameFragment.html | DeleteCookiesFragment.html | DeleteCookies.java | CookiesHaveBeenDeleted.html  
WebAppWithCookies  
  Web Pages  
    META-INF  
    WEB-INF  
    CookiesHaveBe  
    DeleteCookiesF  
    WhatsYourNam  
    index.html  
  Source Packages  
    it.unitn.disi.ron  
      DeleteCooki  
      Welcome.jav  
  Test Packages  
Navigator  
1 <!DOCTYPE html>  
2 <html>  
3 <head>  
4     <title>Cookies have been deleted</title>  
5     <meta charset="UTF-8">  
6     <meta name="viewport" content="width=device-width, initial-scale=1.0">  
7 </head>  
8 <body>  
9     All cookies have been deleted <br>  
10    Go to the <a href="/WebAppWithCookies/welcome">initial page</a>.  
11 </body>  
12 </html>
```

Cookies in action - 3

```
package it.unitn.disi.ronchet.myervlets;

import ...

@WebServlet(urlPatterns = {"/welcome"})
public class Welcome extends HttpServlet {

    String msg;
    boolean isInitialIteration ;

    private void dealWithInvalidCookie() {
        msg = "Sorry, we do not know each other...<br>"
            + "Please introduce yourself.<br>";
        isInitialIteration = true;
    }
}
```

Cookies in action - 4

```
protected void doGet(HttpServletRequest request,
    HttpServletResponse response)
    throws ServletException, IOException {
    isInitialIteration=false;
    // manage params and cookies
    String name = request.getParameter("name");
    if (name != null && ! name.equals("")) {
        // there is the right parameter,
        // no need to read cookie, but we set them
        log("name != null && ! name.equals(\"\")");
        Cookie cookie = new Cookie("name", name);
        msg = "Hi " + name + ", nice to meet you!";
        response.addCookie(cookie); // identity
        Cookie cookie1 = new Cookie("counter", "0");
        response.addCookie(cookie1); // state
        // finished! Go to end
    } else {
```

Cookies in action - 5

```
} else {  
    // no parameter, let's try with cookies  
    Cookie cookies[] = request.getCookies();  
    if (cookies==null || cookies.length == 0) {  
        // no cookies  
        log("no cookies found");  
        dealWithInvalidCookie();  
    } else {  
        Cookie n_Cookie=null; // cookie con il nome  
        Cookie c_Cookie=null; // cookie con il contatore  
        for (Cookie c:cookies) {  
            String cookieName = c.getName();  
            if (cookieName.equals("name")) {  
                n_Cookie=c;  
            } else if (cookieName.equals("counter")) {  
                c_Cookie=c;  
            }  
        }  
        if (n_Cookie==null) {  
            log ("valid cookies not found");  
            // invalid cookie  
            dealWithInvalidCookie();  
        } else {
```



Cookies in action - 6

```
    } else {  
        // ok, the cookie is good!  
        String userName=n_Cookie.getValue();  
        String counterAsString=c_Cookie.getValue();  
        log ("name == "+userName);  
        // let's update the counter, and the cookie  
        int counter=Integer.valueOf(counterAsString)+1;  
        c_Cookie.setValue(""+counter);  
        response.addCookie(c_Cookie);  
        msg = "Hi " + userName + ", welcome back! (" +  
            +counter+")";  
    }  
}
```

Cookies in action - 7

```
// prepare response and send it
    response.setContentType("text/html;charset=UTF-8");
    try (PrintWriter out = response.getWriter()) {
        out.println("<!DOCTYPE html>");
        out.println("<html><body>");
        out.println(msg);
        if (isInitialIteration) {
            request.getRequestDispatcher(
                "WhatsYourNameFragment.html")
                .include(request, response);
        } else {
            request.getRequestDispatcher(
                "DeleteCookiesFragment.html")
                .include(request, response);
        }
        out.println("</body></html>");
    }
}
```

Cookies in action – 8 - deleteCookies

```
@WebServlet(name = "DeleteCookies",
            urlPatterns = {"/deleteCookies"})
public class DeleteCookies extends HttpServlet {

    protected void doGet(HttpServletRequest request,
                        HttpServletResponse response)
        throws ServletException, IOException {
        Cookie cookies[]=request.getCookies();
        if (cookies != null) {
            for (Cookie c : cookies) {
                c.setMaxAge(0);
                response.addCookie(c);
            }
        }
        response.setContentType("text/html; charset=UTF-8");
        request.getRequestDispatcher(
            "CookiesHaveBeenDeleted.html")
            .include(request, response);
    }
}
```